## NSN 5320-01-366-7098

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-366-7098 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Green **Fastener Length:** Between 0.6900 inches and 0.7100 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3765 inches and 0.3813 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** Between 0.3700 inches and 0.3800 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.1900 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

## NSN 5320-01-366-7098

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0