

View Online at <https://aerobasegroup.com/nsn/5320-01-369-3518>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.7615 inches and 0.7635 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0450 inches and 0.0550 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.2950 inches and 0.3150 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.4325 inches and 0.4425 inches

**Thread Qty Per Inch (tpi):**

32

**Thread Size:**

0.1900 inches

**Material:**

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp e4340 or iron alloy 660

**Material Specification:**

Mil-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-5000 military specification 4th material response or ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5626 spec.