Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-369-5738

Fastener Length:

0.350 inches

Head Style:

Universal

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.356 inches and 0.394 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.126 inches and 0.187 inches

Special Features:

Single action, non-shifting installation tools, color code yellow on spindle

Material:

Aluminum alloy 5056 locking ringaluminum alloy 5056 sleevealuminum alloy 2024 stem

Material Specification:

Qq-a-430 federal specification single material response locking ringqq-a-430 federal specification single material response sleeveqq-a-430

federal specification single material response stem

Surface Treatment:

Chromate locking ringchromate sleevechromate stem

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response locking ringmil-c-5541 military specification single treatment response

sleevemil-c-5541 military specification single treatment response stem

Specification Data:

80205-nas1919 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.