

View Online at <https://aerobasegroup.com/nsn/5320-01-369-5747>

**Fastener Length:**

0.523 inches

**Head Style:**

Universal

**Head Height:**

Between 0.067 inches and 0.077 inches

**Shank Diameter:**

Between 0.155 inches and 0.159 inches

**Head Major Diameter:**

Between 0.296 inches and 0.328 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.313 inches and 0.375 inches

**Special Features:**

Single action, non-shifting installation tools, color code yellow on spindle; may be slosh cleaned with mil-c-38736 cleaner before installation

**Material:**

Iron alloy 660 locking ring or nickel alloy r-405 locking ring or nickel alloy 400 locking ringnickel alloy r-405 sleeve or nickel alloy 400 sleeveiron alloy 660 stem

**Material Specification:**

Ams 5737 assn standard 1st material response locking ring or qq-n-281 federal specification 2nd material response locking ring or qq-n-281 federal specification 3rd material response locking ringqq-n-281 federal specification single material response sleeveams 5737 assn standard single material response stem

**Surface Treatment:**

Cadmium sleeve and chromate sleevepassivate stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response sleeveqq-p-35 federal specification single treatment response stem

**Specification Data:**

80205-nas1919 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0