Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-369-5751

## Fastener Length:

0.588 inches

# Head Style:

Universal

# Head Height:

Between 0.067 inches and 0.077 inches

#### Shank Diameter:

Between 0.155 inches and 0.159 inches

#### Shank Style:

Self-plugging mechanically locked stem

### Head Major Diameter:

Between 0.296 inches and 0.328 inches

### **Expansion Device:**

Serrated stem-type w

#### Grip Length:

Between 0.376 inches and 0.437 inches

### **Special Features:**

Single action, non-shifting installation tools, color code yellow on spindle

# Material:

Iron alloy 660 locking ring or nickel alloy r-405 locking ring or nickel alloy 400 locking ringnickel alloy r-405 sleeve or nickel alloy 400 sleeveiron alloy 660 stem

# Material Specification:

Ams 5737 assn standard 1st material response locking ring or qq-n-281 federal specification 2nd material response locking ring or qq-n-281 federal specification 3rd material response locking ringqq-n-281 federal specification single material response sleeveams 5737 assn standard single material response stem

### Surface Treatment:

Passivate stem

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stem

### **Specification Data:**

80205-nas1919 professional/industrial association standard

### Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

### Fiig:

A040a0