

View Online at <https://aerobasegroup.com/nsn/5320-01-369-5760>

Fastener Length:

0.385 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.221 inches and 0.229 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.188 inches and 0.250 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Single action, non-shifting installation tools, color code yellow on spindle

Material:

Aluminum alloy 5056 locking ringaluminum alloy 5056 sleevealuminum alloy 2024 stem

Material Specification:

Qq-a-430 federal specification single material response locking ringqq-a-430 federal specification single material response sleeveqq-a-430 federal specification single material response stem

Surface Treatment:

Chromate locking ringchromate sleevechromate stem

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeve
mil-c-5541 military specification single treatment response stem

Specification Data:

80205-nas1921 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.