

View Online at <https://aerobasegroup.com/nsn/5320-01-369-5781>

**Fastener Length:**

0.323 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Single action, non-shifting installation tools, color code yellow on spindle

**Material:**

Aluminum alloy 5056 locking ringaluminum alloy 5056 sleevealuminum alloy 2024 stem

**Material Specification:**

Qq-a-430 federal specification single material response locking ringqq-a-430 federal specification single material response sleeveqq-a-430 federal specification single material response stem

**Surface Treatment:**

Chromate locking ringchromate sleevechromate stem

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeve  
mil-c-5541 military specification single treatment response stem

**Specification Data:**

80205-nas1921 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.