NSN 5320-01-369-5781

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-369-5781

view offilite at https://aerobasegroup.com/nsn/35220-01-303-5701
Fastener Length:
0.323 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.124 inches and 0.128 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.221 inches and 0.229 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.126 inches and 0.187 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Single action, non-shifting installation tools, color code yellow on spindle
Material:
Aluminum alloy 5056 locking ringaluminum alloy 5056 sleevealuminum alloy 2024 stem
Material Specification:
Qq-a-430 federal specification single material response locking ringqq-a-430 federal specification single material response sleeveqq-a-430
federal specification single material response stem
Surface Treatment:
Chromate locking ringchromate sleevechromate stem
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response locking ringmil-c-5541 military specification single treatment response
sleevemil-c-5541 military specification single treatment response stem
Specification Data:
80205-nas1921 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-c-5541 spec.