

View Online at <https://aerobasegroup.com/nsn/5320-01-369-5785>

Fastener Length:

0.711 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.282 inches and 0.290 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.501 inches and 0.562 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Single action, non-shifting installation tools, color code yellow on spindle

Material:

Iron alloy 660 locking ring or nickel alloy r-405 locking ring or nickel alloy 400 locking ringnickel alloy r-405 sleeve or nickel alloy 400 sleeveiron alloy 660 stem

Material Specification:

Ams 5737 assn standard 1st material response locking ring or qq-n-281 federal specification 2nd material response locking ring or qq-n-281 federal specification 3rd material response locking ringqq-n-281 federal specification single material response sleeveams 5737 assn standard single material response stem

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stem

Specification Data:

80205-nas1921 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0