

View Online at <https://aerobasegroup.com/nsn/5320-01-369-5788>

Fastener Length:

0.336 inches

Head Style:

Universal

Head Height:

Between 0.067 inches and 0.077 inches

Shank Diameter:

Between 0.155 inches and 0.159 inches

Head Major Diameter:

Between 0.296 inches and 0.328 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.126 inches and 0.187 inches

Special Features:

Single action, non-shifting installation tools, color code yellow on spindle

Material:

Iron alloy 660 locking ring or nickel alloy r-405 locking ring or nickel alloy 400 locking ringnickel alloy r-405 sleeve or nickel alloy 400 sleeveiron alloy 660 stem

Material Specification:

Ams 5737 assn standard 1st material response locking ring or qq-n-281 federal specification 2nd material response locking ring or qq-n-281 federal specification 3rd material response locking ringqq-n-281 federal specification single material response sleeveams 5737 assn standard single material response stem

Surface Treatment:

Cadmium sleeve and chromate sleevepassivate stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response sleeveqq-p-35 federal specification single treatment response stem

Specification Data:

80205-nas1919 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0