## NSN 5320-01-369-8339

Blind Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-c-5541 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-369-8339 **Fastener Length:** 0.301 inches **Head Style:** Tapered pan **Head Height:** Between 0.0540 inches and 0.0640 inches **Shank Diameter:** Between 0.1390 inches and 0.1430 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.2380 inches and 0.2620 inches **Expansion Device:** Plain stem-type t **Grip Length:** Between 0.1260 inches and 0.1870 inches Material: Iron alloy 660 locking ring or steel comp 304 locking ringaluminum alloy 5056 sleevesteel comp 8740 stem **Material Specification:** Ams 5731 assn standard 1st material response locking ring or ams 5639 assn standard 2nd material response locking ringqq-a-430 federal specification single material response sleeveams 6322 assn standard single material response stem **Surface Treatment:** Passivate locking ringchromate sleevecadmium stem and chromate stem **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeveqq-p-416, type 2, cl 2 federal specification single treatment response stem Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0