# NSN 5320-01-371-3661

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-371-3661



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.565 inches and 0.585 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

## Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3825 inches and 0.3911 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.245 inches and 0.255 inches

#### Thread Size:

0.190 inches

## Shear Strength:

5380 double pounds per square inch

## **Countersink Angle:**

130.0 degrees

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Surface Treatment:

Aluminum

## Surface Treatment Specification:

Hi-shear spec. 294 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A528u0