

View Online at <https://aerobasegroup.com/nsn/5320-01-371-3665>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.8775 inches and 0.8975 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3825 inches and 0.3911 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.5575 inches and 0.5675 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.1900 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

130.0 degrees

Special Features:

Light orange dye on the chamfer

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0