

View Online at <https://aerobasegroup.com/nsn/5320-01-372-0931>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2120 inches and 0.2209 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.3320 inches and 0.3370 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.5010 inches and 0.5630 inches

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.1380 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Iron alloy 660 boltiron alloy 660 nutiron alloy 660 sleeve

**Material Specification:**

Ams 5732 assn standard single material response boltams 5737 assn standard single material response nutams 5732 assn standard single material response sleeve

**Surface Treatment:**

Passivate boltpassivate nutpassivate sleeve

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response boltmil-s-5002 military specification single treatment response nutmil-s-5002 military specification single treatment response sleeve

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5002 spec.