

View Online at <https://aerobasegroup.com/nsn/5320-01-372-0931>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2120 inches and 0.2209 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.3320 inches and 0.3370 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.5010 inches and 0.5630 inches

Thready Qty Per Inch (tpi):

40

Thread Size:

0.1380 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Iron alloy 660 boltiron alloy 660 nutiron alloy 660 sleeve

Material Specification:

Ams 5732 assn standard single material response boltams 5737 assn standard single material response nutams 5732 assn standard single material response sleeve

Surface Treatment:

Passivate boltpassivate nutpassivate sleeve

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response boltmil-s-5002 military specification single treatment response nutmil-s-5002 military specification single treatment response sleeve

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-5002 spec.