

View Online at <https://aerobasegroup.com/nsn/5320-01-372-0932>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2668 inches and 0.2754 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.4210 inches and 0.4260 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.5010 inches and 0.5630 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.1380 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Iron alloy 660 boltiron alloy 660 nutiron alloy 660 sleeve

**Material Specification:**

Ams 5732 assn standard single material response bolt or ams 5737 assn standard single material response boltams 5732 assn standard single material response nut or ams 5737 assn standard single material response nutams 5732 assn standard single material response sleeve or ams 5737 assn standard single material response sleeve

**Surface Treatment:**

Passivate boltpassivate nutpassivate sleeve

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response boltmil-s-5002 military specification single treatment response nutmil-s-5002 military specification single treatment response sleeve

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5002 spec