# NSN 5320-01-372-0934

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-372-0934

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.2016 inches and 0.2105 inches

# Shank Style:

Threaded self-plugging shank w/sleeve

## Head Major Diameter:

Between 0.296 inches and 0.327 inches

### **Expansion Device:**

Threaded stem

#### Lubrication:

Cetyl alcohol and dry film

### Grip Length:

Between 0.552 inches and 0.592 inches

#### Hardness Rating:

30.0 rockwell c and 45.0 rockwell c

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

### **Special Features:**

High temperature (a-286)

# Material:

Iron alloy 660

### **Material Specification:**

Ams 5732 assn standard 1st material response or ams 5737 federal standard 2nd material response

#### Surface Treatment:

Passivate

### Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

### Shelf Life:

N/a

### Unit Of Measure:

```
--
```

# Demilitarization:

No

### Fiig:

A040a0

# Mil-std (military Standard):

Mil-s-5002 spec.