

View Online at <https://aerobasegroup.com/nsn/5320-01-372-2360>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.0350 inches and 1.0550 inches

Head Style:

Err-090

Head Height:

Between 0.1020 inches and 0.1120 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3266 inches and 0.3276 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.4750 inches and 0.5050 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.4500 inches and 0.5100 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.3125 inches

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.