## NSN 5320-01-372-3029

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-372-3029 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.0550 inches and 2.0750 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1895 inches and 0.1930 inches **Shank Diameter:** Between 0.4521 inches and 0.4526 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.8812 inches and 0.8884 inches **Grip Length:** Between 1.3700 inches and 1.3800 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.4375 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-01-372-3029

Pin-rivet - Page 2 of 2



Fiig:

A528u0