NSN 5320-01-372-7176

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-372-7176 **Thread Direction:** Right-hand Fastener Length: Between 37.95 millimeters and 38.45 millimeters **Head Style:** Err-090 **Head Height:** Between 2.40 millimeters and 2.65 millimeters Width Between Flats: Between 4.02 millimeters and 4.11 millimeters **Shank Diameter:** Between 10.972 millimeters and 10.987 millimeters **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 15.90 millimeters and 16.70 millimeters **Grip Length:** Between 21.87 millimeters and 22.13 millimeters Min. Tensile Strength (psi): 48900 newtons per square millimeter **Thread Size:** 10.0 millimeters Thread Pitch In Millimeters: 1.00 **Shear Strength:** 124500 double newtons per square millimeter **Thread Tolerance Class:** 4h external Material: Titanium alloy **Material Specification:** Ams4971 assn standard single material response **Thread Series Designator:** Iso m **Specification Data:** 73197-hl-610-10-22 manufacturers standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-372-7176

Pin-rivet - Page 2 of 2



Fiig:

A528u0