# NSN 5320-01-372-7177

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-372-7177

# Thread Direction:

**Right-hand** 

## Fastener Length:

Between 38.95 millimeters and 39.45 millimeters

# Head Style:

Err-090

## Head Height:

Between 2.40 millimeters and 2.65 millimeters

## Width Between Flats:

Between 4.02 millimeters and 4.11 millimeters

## Shank Diameter:

Between 10.972 millimeters and 10.987 millimeters

## Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 15.90 millimeters and 16.70 millimeters

## Grip Length:

Between 22.87 millimeters and 23.13 millimeters

## Min. Tensile Strength (psi):

48900 newtons per square millimeter

## Thread Size:

10.0 millimeters

# **Thread Pitch In Millimeters:**

1.00

## Shear Strength:

124500 double newtons per square millimeter

## **Thread Tolerance Class:**

4h external

## Material:

Titanium alloy

## **Material Specification:**

Ams4971 assn standard single material response

## **Thread Series Designator:**

lso m

## **Specification Data:**

73197-hl-610-10-23 manufacturers standard

## Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-372-7177

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

