## NSN 5320-01-372-7187

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-372-7187 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.440 inches and 0.460 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.120 inches and 0.130 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 

5380 double pounds per square inch

## **Special Features:**

Surface coating hi-shear specification 305, type 1, color blue

## Material:

Titanium alloy uns r56400

### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

## **Specification Data:**

73197-hl12vf-6-2 manufacturers standard

#### **Shelf Life:**

N/a

# NSN 5320-01-372-7187

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0