NSN 5320-01-372-7188

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-372-7188

View Online at https://aerobasegroup.com/nsn/5320-01-372-7188
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.503 inches and 0.523 inches
Head Style:
Err-090
Head Height:
Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.183 inches and 0.193 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
3180 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
5380 double pounds per square inch
Special Features:
Surface coating hi-shear specification 305, type 1, color blue
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hl12vf-6-3 manufacturers standard
Shelf Life:

N/a

NSN 5320-01-372-7188

Pin-rivet - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A528u0