# NSN 5320-01-372-7200

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-372-7200

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.573 inches and 0.593 inches

#### Head Style:

Err-090

# Head Height:

Between 0.080 inches and 0.090 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Head Major Diameter:

Between 0.415 inches and 0.440 inches

### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.183 inches and 0.193 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

5820 pounds per square inch

### Thread Size:

0.250 inches

#### Shear Strength:

9300 double pounds per square inch

#### **Special Features:**

Surface coating hi-shear specification 305, type 1, color blue

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# **Thread Series Designator:**

Unjf

# Specification Data:

73197-hl12vf-8-3 manufacturers standard

# Shelf Life:

N/a



# NSN 5320-01-372-7200

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

