NSN 5320-01-372-7203

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-372-7203

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| Between 0.760 inches and 0.780 inches |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.080 inches and 0.090 inches |
| Width Between Flats: |
| Between 0.0947 inches and 0.0967 inches |
| Shank Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.415 inches and 0.440 inches |
| Lubrication: |
| Cetyl alcohol, specification 305, hi-shear corp |
| Grip Length: |
| Between 0.370 inches and 0.380 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 5820 pounds per square inch |
| Thread Size: |
| 0.250 inches |
| Shear Strength: |
| 9300 double pounds per square inch |
| Special Features: |
| Surface coating hi-shear specification 305, type 1, color blue |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 73197-hl12vf-8-6 manufacturers standard |
| Shelf Life: |

N/a

NSN 5320-01-372-7203

Pin-rivet - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

--

Demilitarization:

No

Fiig:

A528u0