NSN 5320-01-372-7217

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-372-7217



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.865 inches and 0.885 inches

Head Style:

Err-090

Head Height:

Between 0.102 inches and 0.112 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.472 inches and 0.505 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.370 inches and 0.380 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

9200 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

14600 double pounds per square inch

Special Features:

Surface coating hi-shear specification 305, type 1, color blue

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-hl12vf-10-6 manufacturers standard

Shelf Life:

N/a

NSN 5320-01-372-7217

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

