

View Online at <https://aerobasegroup.com/nsn/5320-01-372-7224>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.365 inches and 1.385 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.102 inches and 0.112 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.472 inches and 0.505 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.870 inches and 0.880 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

9200 pounds per square inch

**Thread Size:**

0.312 inches

**Shear Strength:**

14600 double pounds per square inch

**Special Features:**

Surface coating hi-shear specification 305, type 1, color blue

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-hl12vf-10-14 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0