## NSN 5320-01-372-7230

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-372-7230

View Online at https://aerobasegroup.com/nsn/5320-01-372-7230
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.740 inches and 1.760 inches
Head Style:
Err-090
Head Height:
Between 0.102 inches and 0.112 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.472 inches and 0.505 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.245 inches and 1.255 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
9200 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
14600 double pounds per square inch
Special Features:
Surface coating hi-shear specification 305, type 1, color blue
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hl12vf-10-20 manufacturers standard
Shelf Life:

N/a

## NSN 5320-01-372-7230

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0