

View Online at <https://aerobasegroup.com/nsn/5320-01-373-2341>

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 31.95 millimeters and 32.45 millimeters

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 4.02 millimeters and 4.11 millimeters

**Shank Diameter:**

Between 10.972 millimeters and 10.987 millimeters

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 16.54 millimeters and 16.68 millimeters

**Grip Length:**

Between 15.87 millimeters and 16.13 millimeters

**Min. Tensile Strength (psi):**

37800 newtons per square millimeter

**Thread Size:**

10.0 millimeters

**Thread Pitch In Millimeters:**

1.00

**Shear Strength:**

124500 double newtons per square millimeter

**Countersink Angle:**

100.0 degrees

**Thread Tolerance Class:**

4h external

**Material:**

Titanium alloy

**Material Specification:**

Ams 4971 assn standard single material response

**Thread Series Designator:**

Iso m

**Specification Data:**

73197-hl-611-10-16 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0