NSN 5320-01-373-2359

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-373-2359

view Online at https://aerobasegroup.com/nsn/3320-01-3/3-2333
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.677 inches and 0.697 inches
Head Style:
Err-090
Head Height:
Between 0.055 inches and 0.065 inches
Width Between Flats:
Between 0.0635 inches and 0.0645 inches
Shank Diameter:
Between 0.1630 inches and 0.1635 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.306 inches and 0.322 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.370 inches and 0.380 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
2180 pounds per square inch
Thread Size:
0.164 inches
Shear Strength:
4010 double pounds per square inch
Special Features:
Surface coating hi-shear specification 305 type 1, color blue
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4867 assn standard single material response
Thread Series Designator:
Unjc
Specification Data:
73197-hl12vf-5-6 manufacturers standard
Shelf Life:

N/a

NSN 5320-01-373-2359

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0