

View Online at <https://aerobasegroup.com/nsn/5320-01-373-2366>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.177 inches and 1.197 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.065 inches

Width Between Flats:

Between 0.0635 inches and 0.0645 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.306 inches and 0.322 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.870 inches and 0.880 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2180 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

4010 double pounds per square inch

Special Features:

Surface coating hi-shear specification 305 type 1, color blue

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4867 assn standard single material response

Thread Series Designator:

Unjc

Specification Data:

73197-hl12vf-5-14 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0