

View Online at <https://aerobasegroup.com/nsn/5320-01-373-2372>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.552 inches and 1.572 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.055 inches and 0.065 inches

**Width Between Flats:**

Between 0.0635 inches and 0.0645 inches

**Shank Diameter:**

Between 0.1630 inches and 0.1635 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.306 inches and 0.322 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 1.245 inches and 1.255 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

2180 pounds per square inch

**Thread Size:**

0.164 inches

**Shear Strength:**

4010 double pounds per square inch

**Special Features:**

Surface coating hi-shear specification 305 type 1, color blue

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4867 assn standard single material response

**Thread Series Designator:**

Unjc

**Specification Data:**

73197-hl12vf-5-20 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0