

View Online at <https://aerobasegroup.com/nsn/5320-01-373-2380>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.003 inches and 1.023 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2021 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.683 inches and 0.693 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

3180 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

6130 double pounds per square inch

Special Features:

Surface coating hi-shear specification 305, type 1, color blue

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unf

Specification Data:

73197-hl112vf-6-11 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0