NSN 5320-01-373-2387

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-373-2387

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.440 inches and 1.460 inches
Head Style:
Err-090
Head Height:
Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.2021 inches and 0.2026 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.120 inches and 1.130 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
3180 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
6130 double pounds per square inch
Special Features:
Surface coating hi-shear specification 305, type 1, color blue
Material:
Titanium alloy
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unf
Specification Data:
73197-hl112vf-6-18 manufacturers standard
Shelf Life:

N/a

NSN 5320-01-373-2387

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0