NSN 5320-01-373-2389

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-373-2389

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| Between 1.565 inches and 1.585 inches |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.064 inches and 0.074 inches |
| Width Between Flats: |
| Between 0.0791 inches and 0.0806 inches |
| Shank Diameter: |
| Between 0.2021 inches and 0.2026 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.357 inches and 0.377 inches |
| Lubrication: |
| Cetyl alcohol, specification 305, hi-shear corp |
| Grip Length: |
| Between 1.120 inches and 1.130 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 3180 pounds per square inch |
| Thread Size: |
| 0.190 inches |
| Shear Strength: |
| 6130 double pounds per square inch |
| Special Features: |
| Surface coating hi-shear specification 305, type 1, color blue |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unf |
| Specification Data: |
| 73197-hl112vf-6-20 manufacturers standard |
| Shelf Life: |

N/a

NSN 5320-01-373-2389

Pin-rivet - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A528u0