NSN 5320-01-373-2404

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-373-2404

View Online at https://aerobasegroup.com/nsn/5320-01-373-2404							
Thread Class:							
3a							
Thread Direction:							
Right-hand							
Fastener Length:							
Between 1.573 inches and 1.593 inches							
Head Style:							
Err-090							
Head Height:							
Between 0.080 inches and 0.090 inches							
Width Between Flats:							
Between 0.0947 inches and 0.0967 inches							
Shank Diameter:							
Between 0.2646 inches and 0.2651 inches							
Shank Style:							
Pin-rivet, straight, threaded							
Head Major Diameter:							
Between 0.415 inches and 0.440 inches							
Lubrication:							
Cetyl alcohol, specification 305, hi-shear corp							
Grip Length:							
Between 1.183 inches and 1.193 inches							
Thready Qty Per Inch (tpi):							
24							
Min. Tensile Strength (psi):							
5820 pounds per square inch							
Thread Size:							
0.312 inches							
Shear Strength:							
10490 double pounds per square inch							
Special Features:							
Surface coating hi-shear specification 305, type 1, color blue							
Material:							
Titanium alloy							
Material Specification:							
Ams 4928 assn standard single material response or ams 4967 assn standard single material response							
Thread Series Designator:							
Unf							
Specification Data:							
73197-hl112vf-8-19 manufacturers standard							
Shelf Life:							
N/o							

N/a

NSN 5320-01-373-2404

Pin-rivet - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A528u0