NSN 5320-01-373-2412

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-373-2412

View Online at https://aerobasegroup.com/nsn/5320-01-373-2412						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Fastener Length:						
Between 1.678 inches and 1.698 inches						
Head Style:						
Err-090						
Head Height:						
Between 0.102 inches and 0.112 inches						
Width Between Flats:						
Between 0.1270 inches and 0.1295 inches						
Shank Diameter:						
Between 0.3271 inches and 0.3276 inches						
Shank Style:						
Pin-rivet, straight, threaded						
Head Major Diameter:						
Between 0.472 inches and 0.505 inches						
Lubrication:						
Cetyl alcohol, specification 305, hi-shear corp						
Grip Length:						
Between 1.183 inches and 1.193 inches						
Thready Qty Per Inch (tpi):						
24						
Min. Tensile Strength (psi):						
9200 pounds per square inch						
Thread Size:						
0.375 inches						
Shear Strength:						
16000 double pounds per square inch						
Special Features:						
Surface coating hi-shear specification 305, type 1, color blue						
Material:						
Titanium alloy						
Material Specification:						
Ams 4928 assn standard single material response or ams 4967 assn standard single material response						
Thread Series Designator:						
Unf						
Specification Data:						
73197-hl112vf-10-2 manufacturers standard						
Shelf Life:						

N/a

NSN 5320-01-373-2412

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A528u0