NSN 5320-01-373-4913

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-373-4913

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.996 inches and 1.021 inches

Head Style:

Flush countersunk

Shank Diameter:

0.326 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.444 inches and 0.494 inches

Tip Diameter:

0.316 inches

Lubrication:

Dry film or cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.615 inches and 0.630 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

One oblong hole 0.120in. Lg. 0.290in. from top of head, thd hole through longitudinal center line of head 8-32unjc-3b

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--



NSN 5320-01-373-4913

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

