## NSN 5320-01-373-4916

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-373-4916 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.896 inches and 0.921 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.389 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.531 inches and 0.583 inches Tip Diameter: 0.382 inches Lubrication: Dry film or cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** One oblong hole 0.120in long 0.280in from top of head, thd hole through longitudinal center line of head 8-32unjc-3b Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-373-4916

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0