NSN 5320-01-373-4917

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-373-4917 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.958 inches and 0.983 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.389 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.531 inches and 0.583 inches **Tip Diameter:** 0.381 inches Lubrication: Dry film or cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.562 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** One oblong hole 0.120in. Lg 0.290in. from top of head, thd hole through longitudinal center line of head 8-32unjc-3b Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Aqq-p-35 federal specification 1st treatment response **Thread Series Designator:** Unjf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5320-01-373-4917

Pin-rivet - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A528u0