

View Online at <https://aerobasegroup.com/nsn/5320-01-373-8751>

**Fastener Length:**

1.336 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.3775 inches and 0.3780 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.555 inches and 0.560 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Dry film or cetyl alcohol or paraffin wax

**Grip Length:**

Between 0.595 inches and 0.656 inches

**Min. Tensile Strength (psi):**

50500 pounds per square inch

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 100.0 degrees

**Special Features:**

Furnished with steel drive nut, color gray, corrosion resistant coating. Complete top surface of head of nut shall be power blasted.

**Material:**

Titanium alloy uns r56400 nutsteel comp 304 sleeve or iron alloy 660 sleeve steel stem

**Material Specification:**

Ams 4928 assn standard all material responses nut or ams 4967 assn standard all material responses nut

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0