

View Online at <https://aerobasegroup.com/nsn/5320-01-373-8751>

Fastener Length:

1.336 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.3775 inches and 0.3780 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.555 inches and 0.560 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or cetyl alcohol or paraffin wax

Grip Length:

Between 0.595 inches and 0.656 inches

Min. Tensile Strength (psi):

50500 pounds per square inch

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Special Features:

Furnished with steel drive nut, color gray, corrosion resistant coating. Complete top surface of head of nut shall be power blasted.

Material:

Titanium alloy uns r56400 nutsteel comp 304 sleeve or iron alloy 660 sleeve steel stem

Material Specification:

Ams 4928 assn standard all material responses nut or ams 4967 assn standard all material responses nut

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0