NSN 5320-01-373-8752

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-373-8752

Fastener Length:
0.995 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.1970 inches and 0.1990 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
Between 0.2700 inches and 0.3016 inches
Expansion Device:
Threaded stem
Lubrication:
Dry film or paraffin wax or cetyl alcohol
Grip Length:
Between 0.532 inches and 0.594 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400 bolttitanium alloy uns r56400 nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve
Material Specification:
Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0