NSN 5320-01-373-8755

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-373-8755

Fastener Length:
1.306 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.1970 inches and 0.1990 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.5716 inches
Expansion Device:
Threaded stem
Lubrication:
Dry film or paraffin wax or cetyl alcohol
Grip Length:
Between 0.845 inches and 0.906 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400 bolttitanium alloy uns r56400 nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve
Material Specification:
Ams 4928 assn standard single material response bolt or ams 4967 assn standard single material response boltams 4928 assn standard
single material response nut or ams 4967 assn standard single material response nut
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0