NSN 5320-01-374-7708

Pin-rivet - Page 1 of 2

Thread Class:

3a

View Online at https://aerobasegroup.com/nsn/5320-01-374-7708



Thread Direction: Right-hand Identification Code Color: Bronze **Fastener Length:** Between 1.598 inches and 1.618 inches **Head Style:** Err-090 **Head Height:** Between 0.078 inches and 0.088 inches Shank Diameter: Between 0.373 inches and 0.374 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.565 inches and 0.600 inches **Tip Diameter:** Between 0.364 inches and 0.368 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: 1.188 inches Min. Tensile Strength (psi): 870000 pounds per square inch **Thread Size:** 0.375 inches Shear Strength: 210000 double pounds per square inch Material: Steel comp 4140 **Material Specification:** Mil-s-5620 military specification single material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-374-7708

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5620 spec.

