NSN 5320-01-375-1266



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-375-1266 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.7860 inches and 1.8260 inches **Head Style:** Err-090 **Head Height:** Between 0.0610 inches and 0.0690 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3980 inches and 0.4130 inches **Grip Length:** Between 1.3760 inches and 1.4380 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.2500 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 **Material Specification:** Aisi 8740 assn standard all material responses or aisi 4340 assn standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas4450 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-375-1266

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0