## NSN 5320-01-375-9799

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-375-9799



#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

#### Fastener Length:

Between 1.177 inches and 1.197 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0635 inches and 0.0645 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.870 inches and 0.880 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

1200 pounds per square inch

#### Thread Size:

0.164 inches

#### Shear Strength:

4010 double pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Surface coating hi-shear specification 305 type 1, color blue

## Material:

Titanium alloy

## Material Specification:

Ams 4928 assn standard single material response or asm 4967 assn standard single material response

## **Thread Series Designator:**

Unc

## Specification Data:

73197-hl11vf-5-14 manufacturers standard

#### Shelf Life:

N/a

# NSN 5320-01-375-9799

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

