## NSN 5320-01-375-9803

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-375-9803

view Online at https://aerobasegroup.com/nsn/5320-01-375-9803
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.490 inches and 1.510 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0635 inches and 0.0645 inches
Shank Diameter:
Between 0.1630 inches and 0.1635 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.2564 inches and 0.2612 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.183 inches and 1.193 inches
Thready Qty Per Inch (tpi):
• • • • • • • • • • • • • • • • • • • •
32
32
32 Min. Tensile Strength (psi):
32  Min. Tensile Strength (psi): 1200 pounds per square inch
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size:
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength:
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch Countersink Angle:
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch Countersink Angle: 100.0 degrees
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch Countersink Angle: 100.0 degrees Special Features:
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Surface coating hi-shear specification 305 type 1, color blue
Min. Tensile Strength (psi):  1200 pounds per square inch Thread Size:  0.164 inches Shear Strength:  4010 double pounds per square inch Countersink Angle:  100.0 degrees Special Features: Surface coating hi-shear specification 305 type 1, color blue Material:
Min. Tensile Strength (psi):  1200 pounds per square inch  Thread Size:  0.164 inches  Shear Strength:  4010 double pounds per square inch  Countersink Angle:  100.0 degrees  Special Features:  Surface coating hi-shear specification 305 type 1, color blue  Material:  Titanium alloy
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Surface coating hi-shear specification 305 type 1, color blue Material: Titanium alloy Material Specification:
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Surface coating hi-shear specification 305 type 1, color blue Material: Titanium alloy Material Specification: Ams 4928 assn standard single material response or asm 4967 assn standard single material response
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Surface coating hi-shear specification 305 type 1, color blue Material: Titanium alloy Material Specification: Ams 4928 assn standard single material response or asm 4967 assn standard single material response Thread Series Designator:
Min. Tensile Strength (psi): 1200 pounds per square inch Thread Size: 0.164 inches Shear Strength: 4010 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Surface coating hi-shear specification 305 type 1, color blue Material: Titanium alloy Material Specification: Ams 4928 assn standard single material response or asm 4967 assn standard single material response Thread Series Designator: Unc

N/a

## NSN 5320-01-375-9803

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0