## NSN 5320-01-375-9809

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-375-9809

view Offilite at https://aerobasegroup.com/hsh/3320-01-3/3-3003
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.323 inches and 1.343 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0635 inches and 0.0645 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Style:
Head Major Diameter:
Between 0.3898 inches and 0.3948 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.933 inches and 0.943 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
3700 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
9300 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Surface coating hi-shear specification 305 type 1, color blue
Material:
Titanium alloy
Material Specification:
Ams 4928 assn standard single material response or asm 4967 assn standard single material response
Thread Series Designator:
Unf
Specification Data:
73197-hl11vf-8-15 manufacturers standard
Shelf Life:
N/a

N/a

## NSN 5320-01-375-9809

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0