NSN 5320-01-375-9813

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-375-9813 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.760 inches and 0.780 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2646 inches and 0.2651 inches **Shank Style: Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 3700 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 10490 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Surface coating hi-shear specification 305 type 1, color blue Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or asm 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:**

73197-hl111vf-8-6 manufacturers standard

Shelf Life:

N/a

NSN 5320-01-375-9813

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0